


A SOUND AS PURE
AS SCANDINAVIAN AIR

Jamo
STUDIO7 SERIES


FIND OUT MORE





Ref Image	Model	Product Details	Type	Color Options	Shipped As	MRP November 2023
	S25F	Enclosure Type :-2 Way Bass Reflex Sensitivity :-90 dB @ 2.83V /1m. Frequency Response :- 69Hz-21kHz HF Drivers :- 1"/2.54cm Vented Tweeter with a fabric dome LF Drivers :- Dual 5.5" / 14 cm woofers - Embossed paper cone with thor's hammer. Maximum Output :- 107dB Continous Power Handling :- 100 W Nominal Impedance :- 4 ohms	Floor standing	Blue Fjord Vinyl Grey Cloud Vinyl	Pair	1,26,300
	S27F	Enclosure Type :-2 Way Bass Reflex Sensitivity :-90 dB @ 2.83V /1m. Frequency Response :- 67Hz-21kHz HF Drivers :- 1"/2.54cm Vented Tweeter with a fabric dome LF Drivers :- Dual 6.69" / 17 cm woofers - Embossed paper cone with thor's hammer. Maximum Output :- 107.8dB Continous Power Handling :- 120 W Nominal Impedance :- 4 ohms	Floor standing	Blue Fjord Vinyl Grey Cloud Vinyl	Pair	1,59,300
	S27FA	Enclosure Type :-2 Way Bass Reflex Sensitivity :-90 dB @ 2.83V /1m. Frequency Response :- 67Hz-21kHz HF Drivers :- 1"/2.54cm Vented Tweeter with a fabric dome LF Drivers :- Dual 6.69" / 17 cm woofers - Embossed paper cone with thor's hammer. Maximum Output :- 107.8dB Continous Power Handling :- 120 W Nominal Impedance :- 4 ohms	Floor standing	Blue Fjord Vinyl Grey Cloud Vinyl	Pair	1,75,800
	C 95 II	Enclosure Type :-2 Way Bass Reflex Sensitivity :-89 dB Frequency Response :- 37Hz-24.000 Hz HF Drivers :- 25 / 1 Silk Dome with Wave Guide LF Drivers :- 2 x 154.4 / 6 HCCC Cone Power Handling (Watts Long / Short Term) :- 165 / 330 W Nominal Impedance :- 6 ohms	Floor standing	Black White Dark Apple	Pair	1,31,800
	C 97 II	Enclosure Type :-3 Way Bass Reflex Sensitivity :-89 dB Frequency Response :- 32Hz-24.000 Hz HF Drivers :- 25 / 1 Silk Dome with Wave Guide LF Drivers :- 2 x 152.4 / 6 HCCC Cone Power Handling :- 180 / 360 W Nominal Impedance :- 6 ohms	Floor standing	Black White Dark Apple	Pair	1,70,300

	D 590	Enclosure Type :-3 Way Bass Reflex Sensitivity :-90 dB Frequency Response :- 35Hz-20.000 Hz HF Drivers :- 25 / 1 Silk Dome LF Drivers :- 2 x 127 / 5 Power Handling (Watts Long / Short Term) :- 200 / 280 W Nominal Impedance :- 4 ohms	Floor standing	Cherry	Pair	1,49,800
---	-------	--	----------------	--------	------	----------


Subwoofers

	S 808 SUB CE	Frequency Response : 39Hz - 180Hz Amplifier Type : Class D Amplifier Power (Cont/Peak) : 50W / 100W Drivers : 20.3mm (8") Polyfiber Woofer Maximum Output : 108dB Speaker Enclosure : MDF Enclosure Type : Bass Reflex via slot port Inputs : RCA Line-In/LFE. Dimensions : 457mm x 354mm x 176mm 18.0" x 13.9" x 6.9"	Subwoofer	Black Walnut White	Single	30,600
---	--------------	--	-----------	--------------------	--------	--------


	Sub C910	Frequency Response : 32Hz - 125Hz Amplifier Type : Class D with Analog Preamp Stage Amplifier Power (Cont/Peak) : 50W / 200W Drivers : 10" Long Throw IMG Maximum Output : 110dB Speaker Enclosure : MDF Enclosure Type :Bass Reflex via Front Firing Inputs :Dual RCA /LFE Line In ,WA-2 Port Dimensions : 400mm x 318 mm x 408mm 15.76" x 12.5" x 16.1"	Subwoofer	Black Dark Apple	Single	50,400
---	----------	---	-----------	------------------	--------	--------

	Sub C912	Frequency Response : 29Hz - 125Hz Amplifier Type : Class D with Analog Preamp Stage Amplifier Power (Cont/Peak) : 75W / 300W Drivers : 12" Long Throw IMG Maximum Output : 114dB Speaker Enclosure : MDF Enclosure Type :Bass Reflex via Front Firing Tube Port Inputs :Dual RCA /LFE Line In ,WA-2 Port Dimensions : 454mm x 356 mm x 480mm 17.89" x 13.99" x 18.88"	Subwoofer	Black Dark Apple	Single	58,600
--	----------	---	-----------	------------------	--------	--------

Surrounds

	C 9 SUR II	Enclosure Type :-3 Way Sealed Sensitivity :-87 dB Frequency Response :- 80Hz-24kHz HF Drivers :- 25 / 1 Silk Dome with Wave Guide LF Drivers :- 101.6 / 4 HCCC Cone Power Handling (Watts Long / Short Term) :- 120 / 240 W Nominal Impedance :- 6 ohms	Surround	Black	Pair	82,300
--	------------	---	----------	-------	------	--------



Centre Speakers

	S7 25C	Enclosure Type :-2 Way Bass Reflex Sensitivity :-90.2dB @ 2.83V /1 m Frequency Response :- 82Hz-21kHz HF Drivers :- 1" / 2.54 cm Vented tweeter with a fabric dome LF Drivers :- Dual 5.5" / 14 cms woofers Embossed Paper Cone with Thor's Hammer Power Handling :- 100 W Nominal Impedance :- 4 ohms	Center Channel Speaker	Blue Fjord Vinyl Grey Cloud Vinyl	Single	49,300
--	--------	---	------------------------	-----------------------------------	--------	--------

	S7 43C	Enclosure Type :-2 Way Bass Reflex Sensitivity :-91.2dB @ 2.83V / 1 m Frequency Response :- 123Hz-21kHz HF Drivers :- 1" / 2.54 cm Vented tweeter with a fabric dome LF Drivers :- Quad 3.3" / 8.4 cm woofers Embossed Paper Cone with Thor's Hammer Power Handling :- 100 W Nominal Impedance :- 4 ohms	Center Channel Speaker	Blue Fjord Vinyl Grey Cloud Vinyl	Single	57,000
	C 9 CEN II	Enclosure Type :-2 Way Bass Reflex Sensitivity :-88dB Frequency Response :- 55Hz-24kHz HF Drivers :- 25 / 1 Silk Dome with Wave Guide LF Drivers :- 2 x 101.6 / 4 HCCC Cone Power Handling (Watts Long / Short Term) :- 140 / 280 Nominal Impedance :- 4 ohms	Center Channel Speaker	Black White Dark Apple	Single	51,500
THX						
	D500 LCR HG Black	Enclosure Type :-3 Way Sealed Sensitivity :-88dB Frequency Response :- 80Hz-20kHz Woofers (mm/ in) : 2 x 140 / 5.50 Midrange (mm/ in) :- 2 x 76 / 3 Power Handling (Watts Long / Short Term) :- 150 / 200 Nominal Impedance :- 4 ohms	L-C-R Channel Speaker	Black White	Single	50,400
	D 500 SUR HG Black	Enclosure Type :-3 Way Closed Dipole Sensitivity :-87dB Frequency Response :- 80Hz-20kHz Woofers (mm/ in) : 1 x 140 / 5.50 Midrange (mm/ in) :- 2 x 76 / 3 Power Handling (Watts Long / Short Term) :- 120 / 170 Nominal Impedance :- 4 ohms	Surround	Black White	Pair	95,400
Studio PDD's						
	S25F. 5.1 Package	S25F 5.1 (S25F Floor Standing Speaker + S25C Center Speaker + S15B Book Shelf Speaker + C910 Subwoofer 10")	Package	Blue Fjord Vinyl Grey Cloud Vinyl Sub :- Black / Dark Apple	Kit	2,94,000
	S27F 5.1 Package	S27F 5.1 (S27F Floor Standing Speaker + S43C Center Speaker + S15B Book Shelf Speaker + C912 Subwoofer 12")	Package	Blue Fjord Vinyl Grey Cloud Vinyl Sub:- Black / Dark Apple	Kit	3,42,900
	C 95 II PDD 5.1 with Sub C910	C 95 II 5.1 (C95 II Floor Standing Speaker + C9 Center Speaker + C9 Surround II + C190 Subwoofer 10")	Package	Black White Dark Apple Sub :-Black / Dark Apple	Kit	3,16,000

	C 97 II PDD 5.1 with Sub C912	C 97 II 5.1 (C 97 II Floor Standing Speaker + C9 Center Speaker + C9 Surround II + C912 Subwoofer 12")	Package	Black White Dark Apple Sub :-Black / Dark Apple	Kit	3,62,700
PPL's						
	PPL	S807 HCS (S807 Floor Standing Speaker + S81 Center Speaker + S801 Book Shelf Speaker)	Package	Black Walnut White	Kit	1,20,400
	PPL	S809 HCS (S809 Floor Standing Speaker + S81Center Speaker + S 801 Book Shelf Speaker)	Package	Black Walnut White	Kit	1,40,200
Bookshelf Speakers						
	S 801	Enclosure Type :-Bass Reflex via Rear Firing Slot Port Sensitivity :- 85dB @ 2.83V /1 m Frequency Response :- 76Hz-26kHz HF Drivers :- 25mm (1") Soft Dome Tweeter LF Drivers :- 102mm (4") Polyfiber Woofer Power Handling :- 60W / 120W Nominal Impedance :- 8 ohms	Bookshelf	Black Walnut White	Pair	22,900
	S 15B	Enclosure Type :-2 Way Bass Reflex Sensitivity :- 86.3dB @ 2.83V /1 m Frequency Response :- 71Hz-22kHz HF Drivers :- 2.5cm (1") Vented Tweeter with A Fabric Dome LF Drivers :- Single 5.5 / 14cm woofer Embossed Paper Cone with Thors Hammer Continous Power Handling :- 85W Nominal Impedance :- 4 ohms	Bookshelf	Blue Fjord Vinyl Grey Cloud Vinyl	Pair	68,000
	S 17B	Enclosure Type :-2 Way Bass Reflex Sensitivity :- 87.2dB @ 2.83V /1 m Frequency Response :- 64Hz-25kHz HF Drivers :- 2.5cm (1") Vented Tweeter with A Fabric Dome LF Drivers :- Single 6.69 / 17cm woofer Embossed Paper Cone with Thors Hammer Continous Power Handling :- 85W Nominal Impedance :- 4 ohms	Bookshelf	Blue Fjord Vinyl Grey Cloud Vinyl	Pair	82,300
	C 91 II	Enclosure Type :-2 Way Bass Reflex Sensitivity :- 86 dB Frequency Response :- 65Hz-24kHz HF Drivers :- 25mm / 1" Neodymium LF Drivers :- 101.6mm / 4" Power Handling (Watts Long / Short Term) :- 100 / 150 W Nominal Impedance :- 6 ohms	Bookshelf	Black White Dark Apple	Pair	61,400

	C 93 II	Enclosure Type :-2 Way Bass Reflex Sensitivity :- 88 dB Frequency Response :- 45Hz-24kHz HF Drivers :- 25mm / 1" Silk Dome with Wave Guide LF Drivers :- 152.4mm / 6 HCCC Cone Power Handling (Watts Long / Short Term) :- 120 / 240 W Nominal Impedance :- 6 ohms	Bookshelf	Black White Dark Apple	Pair	73,500
Aesthetic						
	Studio Cinema 5.1	System Type :- 5.1 Surround with Powered Subwoofer Sensitivity :- Front L/R 86dB Center 88dB / Surrounds 84dB Frequency Response :- 38Hz-20kHz Tweeter :- Front L/R .75" Soft Dome / Center .75" Soft Dome Woofer :- Front L/R 3" Polyfiber Woofer Center :- Dual 3" Polyfiber Woofer Surrounds :- 3" Polyfibre Full Range Woofer :- 8" Downfiring Polyfiber Power Handling :- 60W Continuous / 80W Peak Impedance :- 6 Ohm Minimum, 8 Ohm Nominal (Front L/R, Center, Surrounds)	Satellite Package	Black White	Kit	87,200
Custom Install						
	IW 606 SUR FG II	Woofer (mm / in) :-165mm / 6.5" Midrange (mm / in) :- 2 x 89mm / 3.50" Tweeter (mm / in) :- 2 x 25 / 1 DTT Power (W LONG / SHORT TERM) :- 60 / 120 Frequency Range (Hz) :- 65-22,000 Impedance (Ohm) :- 4-8 Switchable Dimensions HxWxD (mm / in) :- 562mm x 232mm x 107mm / 22.1" x 9.1" x 4.2" Back Box Size (Litre / in3) :- 14 / 850	3-Way In Wall Speaker	White	Pcs	51,500
	IW 626 LCR FG II	Woofer (mm / in) :-2 x 165mm / 6.5" Midrange (mm / in) :- 38mm / 1.50" Tweeter (mm / in) :- 25 / 1 DTT Power (W LONG / SHORT TERM) :- 80 / 160 Frequency Range (Hz) :- 55-22,000 Impedance (Ohm) :- 4-8 Switchable Dimensions HxWxD (mm / in) :- 562mm x 232mm x 107mm / 22.1" x 9.1" x 4.2" Back Box Size (Litre / in3) :- 22 / 1340	3-Way In Wall Speaker	White	Pcs	63,600
	IW 406 FG II	Woofer (mm / in) :- 165mm / 6.5" Midrange (mm / in) :- - Tweeter (mm / in) :- 25 / 1 DTT Power (W LONG / SHORT TERM) :- 60 / 120 Frequency Range (Hz) :- 65-22,000 Impedance (Ohm) :- 4-8 Switchable Dimensions HxWxD (mm / in) :- 325mm x 231mm x 107mm / 12.8" x 9.1" x 4.2" Back Box Size (Litre / in3) :- 14 / 850	2-Way In Wall Speaker	White	Pair	54,400
	IW 425 LCR FG II	Woofer (mm / in) :- 2 x 140mm / 5.5" Midrange (mm / in) :- - Tweeter (mm / in) :- 25 / 1 DTT Power (W LONG / SHORT TERM) :- 60 / 120 Frequency Range (Hz) :- 75-22,000 Impedance (Ohm) :- 4-8 Switchable Dimensions HxWxD (mm / in) :- 395mm x 204mm x 104mm / 15.6" x 8" x 4.1" Back Box Size (Litre / in3) :- 18 / 1100	2-Way In Wall Speaker	White	Pcs	34,400

	<p>IC 408 FG II</p>	<p>Woofers (mm / in) :- 203mm / 8" Midrange (mm / in) :- - Tweeter (mm / in) :- 25mm / 1 DTT Power (W LONG / SHORT TERM) :- 80 / 160 Frequency Range (Hz) :- 55-22,000 Impedance (Ohm) :- 4-8 Switchable Dimensions HxWxD (mm / in) :- 272mm x 112mm / 10.7" x 4.4" Back Box Size (Litre / in3) :- 22 / 1340</p>	<p>2-Way In Wall Speaker</p>	<p>White</p>	<p>Pair</p>	<p>63,600</p>
	<p>6.5CS-T</p>	<p>Woofers (in) :- 6.5" Tweeter (in) :- .5" Power (W LONG / SHORT TERM) :- 25 / 50 Impedance (Ohm) :- 8 Ohms / 70-100 Switchable Dimensions HxD (mm / in) :- 227mm x 81mm 8.9" x 3.2"</p>	<p>White</p>	<p>2-Way 6½"Ceiling</p>	<p>Pair</p>	<p>19,000</p>